

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization International Bureau



(43) International Publication Date  
10 March 2005 (10.03.2005)


PCT

(10) International Publication Number  
**WO 2005/021250 A1**

- (51) International Patent Classification<sup>7</sup>: **B29D 11/00**
- (21) International Application Number:  
**PCT/GB2004/003677**
- (22) International Filing Date: 27 August 2004 (27.08.2004)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:  
0320338.7 29 August 2003 (29.08.2003) GB
- (71) Applicant (*for all designated States except US*): VISAQ LIMITED [GB/GB]; Unit 2 Triton Centre, Premier Way, Abbey Industrial Estate, Romsey SO51 9DJ (GB).
- (72) Inventor; and
- (75) Inventor/Applicant (*for US only*): KELLY, Michael [GB/GB]; 8 The Vincyards, North Baddesley, Southampton SO52 9PP (GB).
- (74) Agents: PLUCKROSE, Anthony, William et al.; Boult Wade Tenant, Verulam Gardens, 70 Gray's Inn Road, London WC1X 8BT (GB).
- (81) Designated States (*unless otherwise indicated, for every kind of national protection available*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*unless otherwise indicated, for every kind of regional protection available*): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

*[Continued on next page]*

(54) Title: A METHOD OF MOULDING CONTACT LENSES AND MOULDING APPARATUS FOR USE IN THE METHOD



(57) Abstract: The present application relates to a method of moulding a contact lens using a male mould (3) and a female mould (5). The method comprises the steps of introducing lens-forming material in a liquid state into the female mould. The male mould is then inserted into the female mould to a first relative position to form an assembly of the male and female moulds in which the moulds together define a moulding cavity (11) and a reservoir (21) for lens-forming material. During the insertion of the male mould to the first position thereof, part of the liquid state lens-forming material is expelled from the moulding cavity to the reservoir. Curing of the lens-forming material is then initiated in the moulding cavity whilst keeping open a pathway between the moulding cavity and

the reservoir so as to allow lens forming material to flow from the reservoir into the moulding cavity to compensate for shrinkage of the lens-forming material during curing. An external force is applied on the assembly of moulds to insert the male mould further into the female mould to thereby close the moulding cavity and to seal off the moulding cavity from the reservoir. The lens-forming material is allowed to complete the transformation to a final, glassy solid state within the sealed moulding cavity. The formed contact lens is removed from the assembly of male and female moulds after the lens forming material has reached the final glassy solid state thereof. The invention also relates to apparatus for moulding a contact lens.

WO 2005/021250 A1



**Declaration under Rule 4.17:**

— *of inventorship (Rule 4.17(iv)) for US only*

**Published:**

— *with international search report*

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

*For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.*